

FLIR E75



FLIR ha rediseñado completamente las cámaras térmicas de la serie Exx para ofrecer un rendimiento, una resolución y una sensibilidad inigualables en una cámara termográfica portátil de este formato.

Calificación: Sin calificación

Precio

[Haga una pregunta sobre este producto](#)

Fabricante: [Flir](#)

Descripción

Cuenta con numerosas funcionalidades útiles para encontrar puntos calientes, detectar los primeros signos de deficiencias en los edificios, solucionar problemas en sistemas eléctricos y mecánicos, y evitar otros problemas antes de que provoquen daños graves.

Prestaciones de la FLIR E75

Visión clara con cualquier ángulo

La pantalla LCD nítida de 4" con ángulo de visión de 160° de gran luminosidad.

Calibración de alta temperatura

La cámara de infrarrojos ofrece amplios rangos de medición (de -20 a 120 °C, de 0 a 650 °C y de 300 °C a 1000 °C).

Interfaz y navegación intuitivas

La pantalla táctil capacitiva y los cómodos botones de menú facilitan la navegación y el control de la cámara térmica con una sola mano.

Mejora superior de escenas MSX®

Incorpora la última versión de la tecnología patentada MSX®, que importa en tiempo real las aristas del espectro visible capturados con la cámara fotográfica a la imagen termográfica, logrando una mejor comprensión de la imagen térmica.

Garantía 2-10 líder en el sector

FLIR respalda la serie Exx con la mejor garantía del mercado, para la batería, el cuerpo y el detector.

Ref. 78501-0101, 78502-0101, 78503-0101, 78504-0101, 78507-0101; 78505-0101, 78506-0101

Imaging and optical data	(para lente 24°)
Infrared resolution	320 x 240 pixels
UltraMax (super-resolution)	Yes
NETD	<0.4° C@30°C (86°F).
Field of view	24°
Minimum focus distance	0.15 m (0.49 ft.)
Minimum focus distance with MSX	0.5 m (1.64 ft.)
Focal length	17 mm (0.67 in.)
Spatial resolution (IFOV)	1.31 mrad/pixel
Available extra lenses	<ul style="list-style-type: none">• 42° (AutoCal)• 14° (AutoCal)
Lens identification f number	Automatic 1.3
Image frequency	30 Hz
Focus	<ul style="list-style-type: none">• Continuous LDM• One-shot LDM• One-shot contrast• Manual
Field of view match	Yes
Digital zoom	1–4x continuous
Detector data	
Focal plane array/spectral range	Uncooled microbolometer/7.5–14 µm
Detector pitch	17 µm
Image presentation	
Resolution	640 x 480 pixels (VGA)
Surface brightness (cd/m2)	400
Screen size	4 in.
Viewing angle	80°
Color depth (bits)	24
Aspect ratio	4:3
Auto-rotation	Yes
Touchscreen	Optically bonded PCAP
Display technology	IPS
Cover glass material	Dragontrail®
Programmable buttons	1
Viewfinder	No
Image adjustment	<ul style="list-style-type: none">• Automatic• Automatic

Image presentation

- maximum
- Automatic
- minimum
- Manual

Image presentation modes

Infrared image	Yes
Visual image	Yes
Thermal fusion	No
MSX	Yes
Picture in Picture	Resizable and movable
Gallery	Yes

Measurement

Camera temperature range

- -20 to 120°C (-4 to 248°F)
- 0 to 650°C (32 to 1202°F)
- Optional 300 to 1000°C (572 to 1832°F)

Object temperature range and accuracy (for ambient temp. 15 to 35°C (59 to 95°F))

- Range -20 to 120°C (-4 to 248°F):
 - -20 to 100°C (-4 to 212°F): ±2°C (± 3.6°F)
 - 100 to 120°C (212 to 248°F): ±2%
- Range 0 to 650°C (32 to 1202°F):
 - 0 to 100°C (32 to 212°F): ±2°C (± 3.6°F)
 - 100 to 650°C (212 to 1202°F): ±2%
- Optional Range 300 to 1000°C (572 to 1832°F): ±2%

Screening mode

Sampling average mode

Recommended temperature range: 30 to 45°C (86 to 113°F) in stable room temperature

Accuracy (drift): ±0.3°C (±0.5°F) [1](#)

Measurement analysis	
Spotmeter	3 in live mode
Area	1 in live mode
Automatic hot/cold detection	Auto-maximum/minimum markers within area
Measurement presets	<ul style="list-style-type: none"> • No measurements • Center spot • Hot spot • Cold spot • User preset 1 • User preset 2
Difference temperature	Yes
Reference temperature	Yes
Emissivity correction	Yes: variable from 0.01 to 1.0 or selected from materials list
Measurement corrections	Yes
External optics/windows correction	Yes
Alarm	
Color alarm (isotherm)	<ul style="list-style-type: none"> • Above • Below • Interval • Condensation (moisture/humidity/dewpoint) • Insulation
Measurement function alarm	Audible/visual alarms (above/below) on any selected measurement function
Set-up	
Color palettes	<ul style="list-style-type: none"> • Iron • Gray • Rainbow • Arctic • Lava • Rainbow HC
Setup commands	Local adaptation of units, language, date and time formats
Languages	21
Service functions	
Camera software update	Using USB cable or SD card
Storage of images	
Storage media	Removable memory; SD card (8 GB)
Time lapse (periodic image storage)	No
Remote control operation	Using USB cable or Wi-Fi
Image file format	Standard JPEG, measurement data included. Infrared-only mode

Image annotations		
Voice	60 seconds built-in microphone and speaker (and via Bluetooth) on still images and video	
Text	Text from predefined list or soft keyboard on touchscreen	
Visual image annotation	Yes	
Image sketch	Yes: on infrared images only	
Sketch	From touchscreen	
METERLiNK	Wireless connection (Bluetooth) to: FLIR meters with METERLiNK	
Compass	Yes	
Laser distance meter information	Yes	
Area measurement information	No	
GPS	Yes: location data automatically added to every still image and the first frame in video from built-in GPS	
Video recording in camera		
Radiometric infrared-video recording	RTRR (.csq)	
Non-radiometric infrared-video recording	H.264 to memory card	
Visual video recording	H.264 to memory card	
Video streaming		
Radiometric infrared-video streaming (compressed)		Over UVC
Non-radiometric video streaming (compressed: IR, MSX, visual, Picture in Picture)		<ul style="list-style-type: none"> • H.264 (AVC) over RTSP (Wi-Fi) • MPEG4 over RTSP (Wi-Fi) • MJPEG over UVC and RTSP (Wi-Fi)
Visual video streaming		Yes
Digital camera		
Resolution	5 MP with LED light	
Focus	Fixed	
Field of view	53° x 41°	
Video lamp	Built-in LED light	
Laser pointer		
Laser alignment	Position is automatically displayed on the infrared image	
Laser distance meter	Activated by a dedicated button	
Laser	Class 2, 0.05–40 m (1.6–131 ft.) ±1% of measured distance	
Data communication interfaces		
Interfaces	USB 2.0, Bluetooth, Wi-Fi, DisplayPort	

Data communication interfaces	
METERLiNK/Bluetooth	Communication with headset and external sensors
Wi-Fi	Peer to peer (ad hoc) or infrastructure (network)
Audio	Microphone and speaker for voice annotation of images
USB	USB Type-C: data transfer/video/power
USB standard	USB 2.0 High Speed
Video out	DisplayPort
Video connector type	DisplayPort over USB Type-C
Radio	
Operating frequency	Bluetooth + EDR/LE: 2402–2480 MHz WLAN 2.4 GHz: 2412–2462 MHz WLAN 5 GHz: 5150–5350 MHz (DFS: only slave mode) Note that frequency band 5150–5350 MHz is for indoor use only, see national regulations.
RF output (EIRP)	Bluetooth + EDR/LE: < 10 dBm WLAN: < 17 dBm
Antenna	Integrated PIFA antenna (gain: maximum 1.4 dBi)
Power system	
Battery type	Rechargeable Li-ion battery
Battery voltage	3.6 V
Battery operating time	> 2.5 hours at 25°C (68°F) and typical use
Charging system	In camera (AC adapter or 12 V from a vehicle) or two-bay charger
Charging time (using two-bay charger)	2.5 hours to 90% capacity with charging status indicated by LEDs
Charging temperature	0°C to +?45°C (+?32°F to +?113°F)?, except for the Korean market: +10°C to +?45°C (+?50°F to +?113°F)?
External power operation	AC adapter 90–260 V AC, 50/60 Hz, or 12 V from a vehicle (cable with standard plug—optional)
Power management	Automatic shut-down

Power system	and sleep mode
Environmental data	
Operating temperature range	-15 to +50°C (5-122°F)
Storage temperature range	-40 to +70°C (-40 to +158°F)
Humidity (operating and storage)	IEC 60068-2-30/24 hours/95% relative humidity 25-40°C (77-104°F)/two cycles
EMC	<ul style="list-style-type: none">• ETSI EN 301 489-1 (radio)• ETSI EN 301 489-17• EN 61000-6-2 (immunity)• EN 61000-6-3 (emission)• FCC 47 CFR Part 15 Class B (emission)
Radio spectrum	<ul style="list-style-type: none">• ETSI EN 300 328• FCC Part 15.249• RSS-247 Issue 2
Encapsulation	IP 54 (IEC 60529)
Shock	25g (IEC 60068-2-27)
Vibration	2g (IEC 60068-2-6)
Drop	Designed for 2 m (6.6 ft.)
Safety	EN/UL/CSA/PSE 60950-1

Comentarios

Aún no hay comentarios para este producto.

// //